Instructions for wear checks of play equipment	СО	The equipment must be checked for correct operation and safety, especially the points listed below:		Proof of maintenance	
Playground  Date of installation	1. 2. 3.	retighten if necessary.  Sphere suspension  Clean with stainless steel spray (www.kim-tec.de) using a clean cloth.  Check that the spheres form an exact line, re-			
<ul> <li>the usage</li> <li>the frequency of use</li> <li>possible vandalism</li> <li>For more details see also "General instructions for maintenance of playgrounds".</li> <li>Impulse Spheres</li> </ul>	5. [ 6.	adjust if necessary (see detailed diagram*).  Replace spheres if necessary.  Structural stability  In order to check for corrosion, uncover the foundation once a year.			
order No. 10.11010  angled rail stop nut M6 top approx. 2-3 mm gap eyebolt M6x40  * Note on step 5: The nuts at the bottom of the angled rails must not be tightened to the end of their threads (approx. 1 mm gap, see detailed diagram).				Special notes, e.g. for repairs	
6	it is	pair not carried out, s still possible to play on equipment pair not carried out,			
	All	work carried out, erything is in order intenance carried out by:			
For spare parts refer to back of page.		Date			

Spare Parts Impulse Spheres Order No. 10.11010



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts**.

## Order No. Spare part

## Order No. Spare part



10.99904

sphere suspension gear with 9 spheres

