nstructions for wear hecks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:		Proof of maintenance	
Playground		Bearings		
Date of installation	1.	Check for firmness, tighten if required.		
Checks depend on the kind of equipment.		Filling		
Any equipment with moving parts must be checked at least twice a year, static equip- ment at least once a year.	2.	Move the pattern board thoroughly at regular intervalls in order to dissolve deposits in the filling.		
Intervals for maintenance work and checks generally depend on:		Cleaning of the surface		
<ul> <li>location</li> <li>kind of use</li> </ul>	3.	Clean the steel surfaces with a special stainless steel cleaning agent.		
<ul> <li>frequency of use</li> <li>possible vandalism</li> <li>For more details see also "General instructions for maintenance of playgrounds".</li> </ul>	4.	Clean the perspex with at mild detergent or a special plastic cleaning agent with anti-static effect. Never use spirit or terpentines for cleaning.		
		Structural stability		
Pattern Board Order No. 10.15005	5.	Check the attachment to the ground once a year for firmness.		
		pair not carried out, it is still possible play on equipment		Special notes (e.g. for repairs):
		pair not carried out,		
The board must be moved vigorously	eq	uipment ist taken out of action		
at regular intervals. Otherwise deposits from the liquid may result in permanent clouding of the pane.		work carried out, erything is in order		
	Ма	aintenance carried out by		
		Date .		