Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground	Wooden parts	
Date of installation	Check for rot and, if necessary, smooth out splinters and round off sharp edges of	
Equipment-specific inspections must be carried out at least twice a year. Intervals for maintenance work and checks generally depend on - location	 cracks. 2. Check that all bolts and screws are tight and retighten if necessary. 3. Check the ash wood rungs of the ladders for wear and tear, the remaining diameter must be at least 30 mm. 	
usagefrequency of usepossible vandalism	Recommendation: apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre.	
For more details see also our general instructions for maintenance of playgrounds!	5. In order to check for rot at wooden parts and steel feet for corrosion, uncover the foundations once a year.	
Transparent Square Tower with roof Order No. L3.20630		Special notes, e.g. for repairs
	Repair not carried out, it is still possible to play on equipment	
	Repair not carried out, equipment is taken out of action	
5	All work carried out, everything is in order	
For spare parts refer to back of page.	Maintenance carried out by:	

Spare parts Transparent Square Tower Order No. L3.20630



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts.**

Order No	o. L3.20630		
Order No.	Spare parts	Order No.	Spare parts
0.92620	Ladder 6 rungs	99.00240 99.00250	Roof spruce, impregnated Roof larch
0.98310	Single rung		
0.30050	Tower cladding, length 3.25 m spruce, impregnated	For further s	spare parts please see spare parts list!
0.30060	Tower cladding, lenght 3.25 m larch		
	Please indicate length and width.		
0.99023	Steel foot for Square Tower - also available for corner posts in oak		