Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially he points listed below:	Proof of maintenance
Playground	PP-Rope	
Date of installation	Check that rope is connected firmly to triangular platform, re-tension if necessary.	arv.
Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static	Ropes	
equipment at least once a year.  Intervals for maintenance work and checks	<ol> <li>Check for wear and tear, especially arouthe staples used to attach the handrail r     If the steel reinforcement is damaged it     incompatible it has produced.</li> </ol>	ropes.
generally depend on  - location - usage	<ul><li>imperative it be replaced.</li><li>Check that the staples holding the rope connected firmly.</li></ul>	s are
<ul><li>frequency of use</li><li>possible vandalism</li></ul>	Important! It should not be possible to form loops v	with
For more details see also "General instructions for maintenance of playgrounds".	the handrail ropes.	VIIII
Rope Bridge of PP-Rope between Triangular Platforms Order No. 3.69865		
3		Special notes, e.g. for repairs
3		Spec
	Repair not carried out, is still possible to play on equipment	
	tepair not carried out, quipment is taken out of action	
	Ill work carried out, verything is in order	
	faintenance carried out by:	P-4
		. Date