

Instructions for wear checks of play equipment

The equipment must be checked for correct operation and safety, especially the points listed below:

Proof of maintenance

Playground.....

Date of installation


Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on


- location
- usage
- frequency of use
- possible vandalism

For more details see also "General instructions for maintenance of playgrounds".


Splash Pump
with fixed water jet
Order No. 5.18050




with mushroom head
Order No. 5.18060



Intake Container
Order No. 5.18052



Foundation Anchor
Order No. 5.18054



Operation

1. Make sure the pump mechanism moves smoothly.

Intake container

2. Check water hoses for wear and tear; replace if necessary. To do this, loosen lid bolts and remove upper part including pump mechanism.
3. Check the float valve for leakage, clean reservoir if necessary.

Cleaning the jet

4. Use a screwdriver to screw off the jet (spraying head), loosen the connecting hose, clean the jet (pipe cleaners are most suitable), re-connect and screw on.

Structural stability

5. Check anchoring to the ground every 12 months, retighten screws and bolts if necessary.

Note

Prior to the start of the frost period, turn off water supply, remove the splash pump and drain the intake container. Open the drainage bolt inside the reservoir to do this. If the splash pump has been removed, you may close the opening using a winter lid.

Repair not carried out, it is still possible to play on equipment

Repair not carried out, equipment is taken out of action

All work carried out, everything is in order

Maintenance carried out by:

..... Date

Special notes, e.g. for repairs