Instructions for wear checks of play equipment

Playground

Date of installation

Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- location
- kind of use
- frequency of use
- possible vandalism

For more details see also "General instructions for maintenance of playgrounds".

Balance Blocks Order No. 6.51700/6.51701/ 6.51702/6.51703/6.51705

	7. 8.
detailed ca.2cm diagram A	
	Rep
detailed	it is
diagram B	Rep equ
5	All v eve
	Mai
For spare parts refer to back of page.	

со	e equipment must be checked for rrect operation and safety, especially e points listed below:	Proo mair	of of Itenance
	Wooden parts		
1.	Check for rot and, if necessary, smooth splinters and round off sharp edges of cracks.		
2.	Recommendation : apply paraffin wax to the upper end grain areas once a year, please refer to order No. 0.90100.		
	Carrying ropes		
3.	Check for wear and tear.		
4.	Check wood connections, re-tension if necessary, they can be retightened by approx. 2 cm (see detailed diagram A).		
5.	Check joint of the carrying rope for wear and tear and make sure connections move smoothly (see detailed diagram B) .		
	Structural stability		
6.	In order to check the steel feet for corrosion, uncover the foundation once a year.		
	Metal/fittings		
7.	Developed sharp edges file stub.		
8.	Expose the pressure bar (steel) under the walkway surface, check for corrosion and retighten the screw connections on the stand posts if necessary.		
			Special notes, e.g. for repairs
	pair not carried out, s still possible to play on equipment		
	pair not carried out, uipment is taken out of action		
	work carried out, erything is in order		
	intenance carried out by:	1	ļ

