Instructions for wear checks of play equipment	CO	The equipment must be checked for correct operation and safety, especially the points listed below:		Proof of maintenance	
Playground		Concrete			
Date of installation Checks depend on the type of equipment.	1.	Check for vandalism, e.g. broken concrete edges and, if necessary, carefully sand down			
Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.		Cleaning			
Intervals for maintenance work and checks generally depend on:	2.	If the concrete surface is soiled, clean using sponge and warm water			
the locationthe usagethe frequency of usepossible vandalism	3.	acetic acid and water with the ratio 1:3 Note To prevent graffiti attacks, the concrete			
For more details see also "General instructions for maintenance of playgrounds".		surface can be treated with Protectosil (www.protectosil.com) Wooden parts			
Curve Order No. 7.89500	4.				
Bench made of Larch Order No. 7.89550	5.	Check that all bolts and screws are tight and retighten if necessary			
2	6.	Recommendation : apply paraffin wax to the upper end grain areas once a year, please refer to order No. 0.90100, 1 litre			
		Structural stability			
4 5 6	7.	Check for a proper and stable stand		Special notes, e.g. for repairs	
		pair not carried out, s still possible to play on equipment			
		pair not carried out, uipment is taken out of action			
	1	work carried out, erything is in order			
	Ma	Maintenance carried out by: Date			