This copy may be copied for maintenance of Nichter pla	, oquipmonii	- raye i
Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground	Slide	
Date of installation	Check for vandalism.	
Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.	Check bolts and screws on the base equipment are tight and retighten if necessary.	
	Structural stability	
Intervals for maintenance work and checks generally depend on	3. In order to check the stability of the foundations or the steel feet for corrosion, uncover the foundation once a year.	
 location usage frequency of use possible vandalism For more details see also our general instructions for maintenance of playgrounds! 	4. Note For slides installed on a slope check that the ground shape has not changed in such a way that foundations are exposed.	
Stainless Steel Slide width 1.00 m, with 1 wave Order No. 3.63390 height 3.00 m Order No. 3.64100 height 3.50 m		Special notes, e.g. for repairs
	Repair not carried out, it is still possible to play on equipment	
	Repair not carried out, equipment is taken out of action	
	All work carried out, everything is in order	
For spare parts refer to back of page.	Maintenance carried out by:	e

Spare parts Stainless Steel Slide Order No. 3.63390/3.64100
Ordor No. Sparo parts



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out

Stainless Steel Slide Order No. 3.63390/3.64100		must not be affected. Therefore, when carrying out repairs it is helpful to only use original parts .	
Order No.	Spare parts		
0.92081	Support for slide, top		
0.92090	Support for slide, bottom		